

ACCESSORIES MCA527

Charger

MCA527 Charger (regulated 12V, 2Amax.)

The charger has a high electromagnetic compatibility and a lockable jack plug. Input voltage: 100-240V AC.



Cable

MCA-PC-USB527

Specified USB2.0 cable (USB-B to USB-A)

Length: 1.5m



MCA-PC Ethernet

Connects the MCA527 to a network.

Length: 1.5m



MCA-Lemo00-BNC

Used for Gate Input for the MCA527.

Length: 1.5m



HV inhibit adapter cable for HPGE- Detectors

Leads the HV inhibit input of the MCA527

(Pin5 on the D9 socket) to a separate BNC socket



MCA-Detector_BNC+SHV+SUB_D

Connects a standard HPGE Detector with the MCA527

1:1 → 1x BNC, 1xSHV, 1xSUB_D9



MCA-Detector_BNC+SUB_D+LEMO

Connects Scionix NaI detector with the MCA527

LEMO (SIZE FFA 2S) to 1xSUB_D9, 1xBNC, 1x SHV



1

HV Power Supplies

High voltage power supply 5000V, 0.2W, positive

Detector high voltage supply +5V to +5000V



High voltage power supply 5000V, 0.2W, negative

Detector high voltage supply -5V to -5000V



High voltage power supply 3600V, 0.25W, positive

Detector high voltage supply +50V to +3600V



High voltage power supply 3600V, 0.25W, negative

Detector high voltage supply -50V to -3600V



2

Other Accessories MCA527

Battery packs

Includes 2 Li-ion batteries, 2600mAh each.



GPS Mouse NAVILOCK NL-603P

GPS mouse with 9-pin Lemo connector for plugging into the extension port of the MCA527



Transport case

Provides space for the MCA, a small detector and Netbook, Palmtop or Pocket PC



We hope that you find the accessories you are looking for.

Feel free to contact us if you have any questions.

Note: Illustrations may differ from the delivery